



Model HVN

## HOT NOTCHER / MODEL HVN

When spreading synthetics or loosely woven knits, it is a common problem for the spread to shift, resulting in distortion in the lay. By using the Hot Notcher HVN to notch intermittently along the edge of the lay, the spread is held securely and can be shifted to the cutting area without worry.

Another useful application for the Hot Notcher is to sear a deep notch into a spread which covers the full area of the table. This deep notch allows the cutter to place the cutting machine baseplate under the spread. Eastman's Hot Notcher is the ideal tool for the job because its capacity for depth adjustment and its variable heat control (400°F to 1250°F/204°C to 677°C) present safe notching of any material up to 10" (25.4 cm) deep.

## MAGNUM™ PUNCH PERFORATOR MODEL MP2

When preparing a marker for repeated use, it is first plotted onto pattern paper or plastic for durability, then transferred to the top layer of fabric on the lay as a guide for cutting out the patterns. One method for copying the marker onto the spread involves punching the marker along pattern lines, positioning the marker on the lay, then "blotting" the marker with pattern powder. When the marker is lifted, it has been transferred to the lay as a series of dots.

The Magnum / Model MP2 is a solid state puncher designed to cut four clean holes per inch (2.54cm) through up to five thicknesses of paper. The punching strength is easily adjustable to accommodate various needs and a single switch allows the operator to free-wheel without punching, single punch or follow the pattern punching.

Three punch sizes are available.



Model MP2



Model LTM

## THREADMARKER / MODEL LTM

Before moving cut patterns to the sewing room, the Threadmarker is used to insert a string through each ply of cloth. The thread is then looped around the patterns and tied to bundle the cloth temporarily while it is transported to next operation. Eastman's Threadmarker ensures matched pairs because it eliminates loose cut patterns of varying sizes.

## MARKING MACHINES

|                                                 | HOT NOTCHER<br>MODEL HVN            | MAGNUM™ PUNCH<br>MODEL MP2               | THREADMARKER<br>MODEL LTM                       |
|-------------------------------------------------|-------------------------------------|------------------------------------------|-------------------------------------------------|
| MOTORS:<br>110v, 1 ph<br>220v, 1ph<br>220v, 3ph | Available<br>Available<br>Available | Available<br>Available<br>Available      | N / Available<br>N / Available<br>N / Available |
| TEMPERATURE CONTROL                             | Standard                            | Standard                                 | N / Available                                   |
| SINGLE PUNCH TRIGGER                            | N / Available                       | N / Available                            | N / Available                                   |
| WEIGHT                                          | 14 lbs., 4 oz.<br>6.75 kg.          | 8 lbs<br>3.63 kg.                        | 13 lbs., 3 oz.<br>5.75 kg.                      |
| MARK DIAMETER                                   | N / Available<br>N / Available      | 1/16" 3/32" 1/8"<br>1.59mm 2.38mm 3.18mm | 3/64" 1/16" 5/64"<br>1.19mm 1.59mm 1.98mm       |
| MARK DEPTH CAPACITY                             | 10"<br>25.4 cm                      | N / Available                            | 2" 4" 6"<br>5.08mm 10.2mm 15.2mm                |